


Part Number	<b>ADP250E305J</b>		Revision
Customer P/N			Revision
Capacitance	<b>3</b>	uF.	Tolerance <b>5%</b>
Voltage	<b>250</b>	VAC	
Dielectric	<b>Metallized Polypropylene</b>		
Terminal Type	<b>Single .250" X .03" Quick Connect Terminals</b>		
Operating Temperature	<b>-25</b>	to	<b>85 °C.</b>
Dissipation Factor	<b>0.001</b>	maximum	@ 60 Hz.

# MOTOR Capacitors, Inc.

**Motor Capacitors, Inc.**  
 335 Beinoris Drive  
 Wood Dale, Illinois 60191  
 773-774-6666 (Phone) | 773-774-6690 (Fax)  
[www.capacitorindustries.com](http://www.capacitorindustries.com)  
[info@capacitorindustries.com](mailto:info@capacitorindustries.com)

	Dimension	Tolerance
Width (W)	<b>1.53</b>	<b>0.03</b>
Thickness (T)	<b>0.67</b>	<b>0.03</b>
Height (H)	<b>1.02</b>	<b>0.03</b>
Total Thickness (Tt)	<b>1.10</b>	<b>0.06</b>
Mounting Hole	<b>0.17</b>	<b>0.01</b>

*Dimensions in inches*



Stamping	<b>ADP</b>
	<b>3 uF 5% 250 VAC</b>
	<b>-25 - +85 C.</b>
	<b>50 - 60 Hz.</b>
	<b>Motor Cap</b>
	<b>ЯU, сЯU RoHs</b>



G = RoHs compliant

**UL Approved Capacitor**



Approval JD Aldana  
 Date January 31, 2000