

# SEI-CAPACITORS

SEI Capacitors, Inc.


335 Beinoris Drive, Wood Dale, IL 60191

Phone: 773-774-6666

Fax: 773-774-6690

www.capacitorindustries.com

## ALUMINUM ELECTROLYTIC CAPACITORS PART NUMBERING SYSTEM



Series
<i>Car Audio Capacitors</i> i.e.: CD98SK
<i>Computer Grade Capacitors</i> i.e.: CDIN CD92 CD92L CD13N CD13L CD92H
<i>Miniature Capacitors</i> i.e.: CD110X CD110XC CD11A CD95B CD113H CD117H CD288H CD288HL CD11H CD26L CD26H CDME CD26J
<i>Non-Polarized Capacitors</i> i.e.: CDVB CD50BP CD71 CD71C CD72 CDS
<i>Photo Flash Capacitors</i> i.e.: CD17S CD17FX
<i>Snap-In Capacitors</i> i.e.: CD292 CD293 CD295 CD297 CD294 CD296 CD298

Voltage	
VDC	Code
4	0G
6.3	0J
10	1A
16	1C
20	1D
25	1E
35	1V
40	1G
50	1H
63	1J
80	1K
100	2A
120	2B
160	2C
180	2K
200	2D
250	2E
315	2F
330	2T
350	2V
360	2X
400	2G
420	2N
450	2W
500	2H
550	2Y

Capacitance	
uF	Code
0.1	0R1
0.22	R22
0.33	R33
0.47	R47
0.68	R68
1	010
2.2	2R2
3.3	3R3
4.7	4R7
6.8	6R8
10	100
22	220
33	330
47	470
68	680
100	101
120	121
150	151
180	181
220	221
330	331
470	471
680	681
1,000	102
1,200	122
2,200	222
3,300	332
4,700	472
10,000	103
22,000	223
33,000	333
47,000	473
68,000	683
100,000	104
220,000	224
330,000	334
470,000	474
680,000	684
1,000,000	105
1,500,000	155

Tolerance	
%	Code
+5	J
-5	J
+10	K
-10	K
+15	L
-15	L
+20	M
-20	M
+30	F
0	F
+30	Q
-10	Q
+20	R
0	R
+50	T
-10	T
+75	U
-10	U
+20	V
-10	V
+30	N
-30	N
+50	S
-20	S

Dimensions
[Diameter] X [Height]
(in millimeters)

Example:

**CD98SK-1E504M76X155**

Series: **CD98SK** (Car Audio Capacitors)

Voltage: **1E** = 25 VDC

Capacitance: **504** = 500,000 uF

Tolerance: **M** = ± 20%

Diameter: **76** mm

Height: **155** mm