


Part Number	CBB65-250R706		Revision
Customer P/N			Revision
Capacitance	70	μ F.	Tolerance 5.0%
Voltage	250	VAC	
Dielectric	Metallized Polypropylene		
Terminal Type	.250" Quad-Spade Quick Connect Terminals		
Operating Temperature	-40 °C.-		85 °C.
Dissipation Factor	0.001	maximum	@ 60 Hz.

MOTOR Capacitors, Inc.

Motor Capacitors, Inc.
335 Beinoris Drive
Wood Dale, Illinois 60191
773-774-6666 (Phone) | 773-774-6690 (Fax)
www.capacitorindustries.com
info@capacitorindustries.com


	Dimension	Tolerance
Diameter (D) Case/Cover	1.97/2.06	0.06
Case Height (H)	3.94	0.06
Terminal Height (K)	0.56	ref.
Terminal-Terminal (M)	0.81	ref.
Insulating Cup (dia.)	0.74	

Dimensions in inches



Stamping

Wuxi - Motor Cap
CBB65-250R706
70uF 5% 250 VAC
-40 - +85 C. 50/60 Hz.

Protected 10,000 AFC 

Non PCB **RU** **cRU** **Date Code** **RoHS**

Approval : *J.D. Aldana*
Date : **November 22, 2005**