

Part Number	CBB65-330V256	Revision	E
Customer P/N	K01666-0013	Revision	E
Capacitance	25	uF.	Tolerance 5.0%
Voltage	330	VAC	
Dielectric	Metallized Polypropylene		
Terminal Type	.250" Quad-Spade Quick Connect Terminals		
Operating Temperature	-40 °C.-	85 °C.	
Dissipation Factor	0.001	maximum	@ 60 Hz.

MOTOR Capacitors, Inc.

Motor Capacitors, Inc.
 335 Beinoris Drive
 Wood Dale, Illinois 60191
 773-774-6666 (Phone) | 773-774-6690 (Fax)
www.capacitorindustries.com
info@capacitorindustries.com

	Dimension	Tolerance
Case / Cover Width (W)	2.80/2.87	0.06
Case / Cover Thickness (T)	1.80/1.87	0.06
Case Height (H)	3.90	0.06
Terminal Height (K)	0.56	ref.
Terminal-Terminal (M)	0.81	ref.
Insulating Cup (dia.)	0.74	


Dimensions in inches



Stamping

Wuxi - Motor Cap
CBB65-330V256
25uF 5% 330 VAC
-40 - +85 C. 50/60 Hz.
K01666-0013
Protected 10,000 AFC

Non PCB **RU** **cRU** **Date Code** **RoHS**



Approval: J. D. Aldana
 Date: January 29, 2003