

Part Number	<b>CBB65-370R256-M1</b>	Revision	
Customer P/N	<b>195-200-1028</b>	Revision	
Capacitance	<b>25</b>	$\mu\text{F.}$	Tolerance <b>5.0%</b>
Voltage	<b>370</b>	VAC	
Dielectric	<b>Metallized Polypropylene</b>		
Terminal Type	<b>.250" Quad-Spade Quick Connect Terminals</b>		
Operating Temperature	<b>-40 °C.-</b>	<b>85 °C.</b>	
Dissipation Factor	<b>0.001</b>	maximum @ 60 Hz.	

# MOTOR Capacitors, Inc.

**Motor Capacitors, Inc.**  
**335 Beinoris Drive**  
**Wood Dale, Illinois 60191**  
**773-774-6666 (Phone) | 773-774-6690 (Fax)**  
[www.capacitorindustries.com](http://www.capacitorindustries.com)  
[info@capacitorindustries.com](mailto:info@capacitorindustries.com)

	Dimension	Tolerance
Diameter (D) Case/Cover	<b>1.75</b>	<b>0.06</b>
Case Height (H)	<b>3.00</b>	<b>0.06</b>
Terminal Height (K)	<b>0.56</b>	<b>ref.</b>
Terminal-Terminal (M)	<b>0.81</b>	<b>ref.</b>
Insulating Cup (dia.)	<b>0.74</b>	



*Dimensions in inches*

Stamping

**Wuxi - Motor Cap**  
**CBB65-370R256-M1**  
**25uF 5% 370 VAC**  
**-40 - +85 C. 50/60 Hz.**  
**195-200-1028**

**Protected 10,000 AFC**

**Non PCB    RU    cRU    Date Code    RoHS**

Approval : *J.D. Aldana*  
Date : March 8, 2006

