

Part Number	CBB65-370R306-M4	Revision
Customer P/N	18-1902-69 9181009-16 HC150244	Revision
Capacitance	30	uF. Tolerance 5.0%
Voltage	370	VAC
Dielectric	Metallized Polypropylene	
Terminal Type	.250" Quad-Spade Quick Connect Terminals	
Operating Temperature	-25 °C.-	70 °C.
Dissipation Factor	0.001	maximum @ 60 Hz.

MOTOR Capacitors, Inc.

Motor Capacitors, Inc.
335 Beinoris Drive
Wood Dale, Illinois 60191
773-774-6666 (Phone) | 773-774-6690 (Fax)
www.capacitorindustries.com
info@capacitorindustries.com

	Dimension	Tolerance
Diameter (D) Case/Cover	1.77/1.87	0.03
Case Height (H)	3.00	0.06
Terminal Height (K)	0.50	ref.
Terminal-Terminal (M)	0.81	ref.
Insulating Cup (dia.)	0.74	

Dimensions in inches


Stamping

Wuxi - Motor Cap
CBB65-370R306-M4
30uF 5% 370 VAC
-25 - +70 C. 50/60 Hz.

18-1902-69 9181009-16 HC150244

Protected 10,000 AFC CE VDE cRU[®] US

Non PCB RU cRU Date Code RoHS



Capacitor must be stamped with Customer's P/N Bar Code

Approval : J.D. Aldana
Date : February 22, 2016