


Part Number	<b>CBB65-370R506-M3</b>	Revision	
Customer P/N	<b>195-200-1030</b>	Revision	
Capacitance	<b>50</b>	uF.	Tolerance <b>5.0%</b>
Voltage	<b>370</b>	VAC	
Dielectric	<b>Metallized Polypropylene</b>		
Terminal Type	<b>.250" Quad-Spade Quick Connect Terminals</b>		
Operating Temperature	<b>-40 °C.</b>		<b>85 °C.</b>
Dissipation Factor	<b>0.001</b>	maximum	@ 60 Hz.

# MOTOR Capacitors, Inc.

**Motor Capacitors, Inc.**  
335 Beinoris Drive  
Wood Dale, Illinois 60191  
773-774-6666 (Phone) | 773-774-6690 (Fax)  
[www.capacitorindustries.com](http://www.capacitorindustries.com)  
[info@capacitorindustries.com](mailto:info@capacitorindustries.com)

	Dimension	Tolerance
Diameter (D) Case/Cover	<b>1.97/2.07</b>	<b>0.06</b>
Case Height (H)	<b>3.75</b>	<b>0.06</b>
Terminal Height (K)	<b>0.56</b>	ref.
Terminal-Terminal (M)	<b>0.81</b>	ref.
Insulating Cup (dia.)	<b>0.74</b>	


*Dimensions in inches*



Stamping

**Wuxi - Motor Cap**  
**CBB65-370R506-M3**  
**50uF 5% 370 VAC**  
**-40 - +85 C. 50/60 Hz.**  
**195-200-1030**  
**Protected 10,000 AFC**

**Non PCB**    **RU**    **cRU E235355**    **Date Code**    **RoHS**




Approval : \_\_\_\_\_ *J.D. Aldana* \_\_\_\_\_  
Date : **March 8, 2006**