


Part Number	CBB65-370R806-M2		Revision
Customer P/N			Revision
Capacitance	80	uF.	Tolerance 5.0%
Voltage	370	VAC	
Dielectric	Metallized Polypropylene		
Terminal Type	.250" Quad-Spade Quick Connect Terminals		
Operating Temperature	-40 °C.-	85 °C.	
Dissipation Factor	0.001	maximum	@ 60 Hz.

MOTOR Capacitors, Inc.


Motor Capacitors, Inc.
 335 Beinoris Drive
 Wood Dale, Illinois 60191
 773-774-6666 (Phone) | 773-774-6690 (Fax)
www.capacitorindustries.com
info@capacitorindustries.com

	Dimension	Tolerance
Diameter (D) Case/Cover	2.25	0.06
Case Height (H)	4.72	0.06
Terminal Height (K)	0.56	ref.
Terminal-Terminal (M)	0.81	ref.
Insulating Cup (dia.)	0.74	

Dimensions in inches



Stamping
Wuxi - Motor Cap
CBB65-370R806-M2
80uF 5% 370 VAC
-40 - +85 C. 50/60 Hz.

Protected 10,000 AFC 
 Non PCB RU cRU Date Code RoHS

Approval : *J.D. Aldana*
 Date : April 30, 2013