

| | | | |
|-----------------------|-------------------------------------------------|---------------|-----------------------|
| Part Number | CBB65-370V156A | Revision | |
| Customer P/N | 301132728 | Revision | |
| Capacitance | 15 | uF. | Tolerance 5.0% |
| Voltage | 370 | VAC | |
| Dielectric | Metallized Polypropylene | | |
| Terminal Type | .250" Quad-Spade Quick Connect Terminals | | |
| Operating Temperature | -40 °C.- | 85 °C. | |
| Dissipation Factor | 0.001 | maximum | @ 60 Hz. |

MOTOR Capacitors, Inc.

Motor Capacitors, Inc.
335 Beinoris Drive
Wood Dale, Illinois 60191
773-774-6666 (Phone) | 773-774-6690 (Fax)
www.capacitorindustries.com
info@capacitorindustries.com

| | Dimension | Tolerance |
|----------------------------|------------------|------------------|
| Case / Cover Width (W) | 2.03/2.16 | 0.03 |
| Case / Cover Thickness (T) | 1.23/1.31 | 0.03 |
| Case Height (H) | 2.98 | 0.03 |
| Terminal Height (K) | 0.56 | ref. |
| Terminal-Terminal (M) | 0.81 | ref. |
| Insulating Cup (dia.) | 0.74 | |


Dimensions in inches



Stamping

Anhui - Motor Cap
CBB65-370V156A
15uF 5% 370 VAC
-40 - +85 C. 50/60 Hz.
301132728
Protected 10,000 AFC

Non PCB **RU** **Date Code** **RoHS**




Approval: *J. D. Aldana*
Date February 23, 2009