

Part Number	CBB65-370V405-PB	Revision	1
Customer P/N	6100-9120	Revision	1
Capacitance	4	uF.	Tolerance 10.0%
Voltage	370	VAC	
Dielectric	Metallized Polypropylene		
Terminal Type	.250" Quad-Spade Quick Connect Terminals		
Operating Temperature	-40 °C.-	85 °C.	
Dissipation Factor	0.001	maximum	@ 60 Hz.

MOTOR Capacitors, Inc.

Motor Capacitors, Inc.
335 Beinoris Drive
Wood Dale, Illinois 60191
773-774-6666 (Phone) | 773-774-6690 (Fax)
www.capacitorindustries.com
info@capacitorindustries.com

	Dimension	Tolerance
Case / Cover Width (W)	2.03/2.16	0.03
Case / Cover Thickness (T)	1.23/1.31	0.03
Case Height (H)	2.38	max.
Terminal Height (K)	0.56	ref.
Terminal-Terminal (M)	0.81	ref.
Insulating Cup (dia.)	0.74	


Dimensions in inches



Stamping

Wuxi - Motor Cap
CBB65-370V405-PB
4uF 10% 370 VAC
-40 - +85 C. 50/60 Hz.
6100-9120
Protected 10,000 AFC

Non PCB **RU** **cRU** **Date Code** **RoHS**



Painted Black Enamel

Approval: *J. D. Aldana*
Date January 2, 2003