

|                       |   |               |             |
|-----------------------|---|---------------|-------------|
| Part Number           | <b>CBB65-370V505-M2</b>                         | Revision      | <b>M</b>    |
| Customer P/N          | <b>1499-542</b>                                 | Revision      | <b>M</b>    |
| Capacitance           | <b>5</b>  | uF.           | <b>5.0%</b> |
| Voltage               | <b>370</b>                                      | VAC           |             |
| Dielectric            | <b>Metallized Polypropylene</b>                 |               |             |
| Terminal Type         | <b>.250" Quad-Spade Quick Connect Terminals</b> |               |             |
| Operating Temperature | <b>-25 °C.-</b>                                 | <b>85 °C.</b> |             |
| Dissipation Factor    | <b>0.001</b>                                    | maximum       | @ 60 Hz.    |

# MOTOR Capacitors, Inc.

Motor Capacitors, Inc.  
 335 Beinoris Drive  
 Wood Dale, Illinois 60191  
 773-774-6666 (Phone) | 773-774-6690 (Fax)  
[www.capacitorindustries.com](http://www.capacitorindustries.com)  
[info@capacitorindustries.com](mailto:info@capacitorindustries.com)

|                            | Dimension        | Tolerance   |
|----------------------------|------------------|-------------|
| Case / Cover Width (W)     | <b>2.03/2.16</b> | <b>0.03</b> |
| Case / Cover Thickness (T) | <b>1.23/1.31</b> | <b>0.03</b> |
| Case Height (H)            | <b>2.38</b>      | <b>0.06</b> |
| Terminal Height (K)        | <b>0.56</b>      | <b>ref.</b> |
| Terminal-Terminal (M)      | <b>0.81</b>      | <b>ref.</b> |
| Insulating Cup (dia.)      | <b>0.74</b>      |             |

*Dimensions in inches*




Stamping

**Wuxi - Motor Cap**  
**CBB65-370V505-M2**  
**5uF 5% 370 VAC**  
**-25 - +85 C. 50/60 Hz.**  
**1499-542**

**Protected 10,000 AFC**

**Non PCB**    **RU**    **cRU**    **Date Code**    **RoHS**




Approval: *J. D. Aldana*  
 Date July 15, 2004