Part Number	**CBB65-440V1255**		Revision	**B**
Customer P/N	**K01666-0062**		Revision	**B**
Capacitance	**12.5**	uF.	Tolerance	**5.0%**
Voltage	**440**	VAC		
Dielectric	**Metallized Polypropylene**			
Terminal Type	**.250" Quad-Spade Quick Connect Terminals**			
Operating Temperature	**-40** °C.-	**85** °C.		
Dissipation Factor	**0.001**	maximum @ 60 Hz.		

MOTOR
Capacitors, Inc.

Motor Capacitors, Inc.
335 Beinoris Drive
Wood Dale, Illinois 60191
773-774-6666 (Phone) | 773-774-6690 (Fax)
www.capacitorindustries.com
info@capacitorindustries.com

	Dimension	Tolerance
Case / Cover Width (W)	**2.80/2.87**	**0.06**
Case / Cover Thickness (T)	**1.80/1.87**	**0.06**
Case Height (H)	**3.06**	**0.06**
Terminal Height (K)	**0.56**	**ref.**
Terminal-Terminal (M)	**0.81**	**ref.**
Insulating Cup (dia.)	**0.74**	

Dimensions in inches



Stamping

Wuxi - Motor Cap
CBB65-440V1255
12.5uF 5% 440 VAC
-40 - +85 C. 50/60 Hz.
K01666-0062
Protected 10,000 AFC
Non PCB ЯU cЯU Date Code RoHS

Approval: *J.D. Aldana*
Date **March 24, 2003**