


Part Number	CBB65-660V406		Revision	
Customer P/N			Revision	
Capacitance	40	uF.	Tolerance	5.0%
Voltage	660	VAC		
Dielectric	Metallized Polypropylene			
Terminal Type	.250" Quad-Spade Quick Connect Terminals			
Operating Temperature	-40 °C.-		85 °C.	
Dissipation Factor	0.001	maximum	@ 60 Hz.	

MOTOR Capacitors, Inc.

Motor Capacitors, Inc.
335 Beinoris Drive
Wood Dale, Illinois 60191
773-774-6666 (Phone) | 773-774-6690 (Fax)
www.capacitorindustries.com
info@capacitorindustries.com

	Dimension	Tolerance
Case / Cover Width (W)	3.66	0.03
Case / Cover Thickness (T)	1.97	0.03
Case Height (H)	4.75	max.
Terminal Height (K)	0.56	ref.
Terminal-Terminal (M)	0.81	ref.
Insulating Cup (dia.)	0.74	
<i>Dimensions in inches</i>		



Stamping	Wuxi - Motor Cap
	CBB65-660V406
	40 uF 5% 660 VAC
	-40 - +85 C. 50/60 Hz.
	Protected 10,000 AFC
	Non PCB Date Code RoHs

Approval: J.D. Aldana
Date June 28, 2005