

Part Number	CBB65-660V506		Revision
Customer P/N			Revision
Capacitance	50	uF.	Tolerance 5.0%
Voltage	660	VAC	
Dielectric	Metallized Polypropylene		
Terminal Type	.250" Quad-Spade Quick Connect Terminals		
Operating Temperature	-40 °C.-	85 °C.	
Dissipation Factor	0.001	maximum	@ 60 Hz.

MOTOR Capacitors, Inc.

Motor Capacitors, Inc.
 335 Beinoris Drive
 Wood Dale, Illinois 60191
 773-774-6666 (Phone) | 773-774-6690 (Fax)
www.capacitorindustries.com
info@capacitorindustries.com

	Dimension	Tolerance
Case / Cover Width (W)	3.54	0.03
Case / Cover Thickness (T)	1.87	0.03
Case Height (H)	5.12	0.03
Terminal Height (K)	0.56	ref.
Terminal-Terminal (M)	0.81	ref.
Insulating Cup (dia.)	0.74	

Dimensions in inches



Stamping

Wuxi - Motor Cap
CBB65-660V506
50 uF 5% 660 VAC
-40 - +85 C. 50/60 Hz.

Protected 10,000 AFC
Non PCB Date Code RoHs

Approval: J. D. Aldana
 Date **March 12, 2012**