

Part Number	CBB65E-660V206		Revision
Customer P/N			Revision
Capacitance	20	uF.	Tolerance 5.0%
Voltage	660	VAC	
Dielectric	Metallized Polypropylene		
Terminal Type	.250" Quad-Spade Quick Connect Terminals		
Operating Temperature	-40 °C.-	70 °C.	
Dissipation Factor	0.001	maximum	@ 60 Hz.

MOTOR Capacitors, Inc.

Motor Capacitors, Inc.
 335 Beinoris Drive
 Wood Dale, Illinois 60191
 773-774-6666 (Phone) | 773-774-6690 (Fax)
www.capacitorindustries.com
info@capacitorindustries.com

	Dimension	Tolerance
Case / Cover Width (W)	2.78	0.06
Case / Cover Thickness (T)	1.77	0.06
Case Height (H)	4.92	0.06
Terminal Height (K)	0.56	ref.
Terminal-Terminal (M)	0.81	ref.
Insulating Cup (dia.)	0.74	ref.

Dimensions in inches



Stamping

Wuxi - Motor Cap
CBB65E-660V206
20 uF 5% 660 VAC
-40 - +70 C. 50/60 Hz.

S2 - Protected 10,000 AFC
Non PCB Date Code RoHS

EIA Standard 456 Extended Life 60,000 HOURS

Approval: J.D. Aldana
 Date September 14, 2016