

Part Number	RPC3Y706		Revision	
Customer P/N	416.10.67		Revision	
Capacitance	70	uF.	Tolerance	5%
Voltage	450	VAC		
Dielectric	Metallized Polypropylene			
Terminal Type	Insulated Bipolar Cable			
Operating Temperature	-25	85	°C.	
Dissipation Factor	0.0015	maximum	@ 60 Hz.	


# MOTOR


## Capacitors, Inc.

Motor Capacitors, Inc.  
 335 Beinoris Drive  
 Wood Dale, Illinois 60191  
 773-774-6666 (Phone) | 773-774-6690 (Fax)  
[www.capacitorindustries.com](http://www.capacitorindustries.com)  
[info@capacitorindustries.com](mailto:info@capacitorindustries.com)

	Dimension	Tolerance
Diameter (D)	1.96	0.03
Height (H)	4.75	0.03
Wire Length (G)	8.00	0.50
Wire Gauge (Gw)	18	AWG
Wire Color (Cw)	Black	

*Dimensions in inches*

<b>Stamping</b>  	Logo / Ducati
	RP-3 SH S0
	70 uf., +/- 5% 400/450 VAC
	25/085/21 50/60 Hz
	CE
	Datecode



Note: Y style terminal

Engineer J.D. Aldana  
 Date July 12, 2024